



**TRADING &  
MANUFACTURING**

**SUNWAY COATING SOLUTIONS SDN BHD 200201024249**  
A member of Sunway Group

## **TECHNICAL INFORMATION LEAFLET**

### **PRODUCT : SUNCOT Multi Sealer (SMS 45)**

SUNCOT Multi Sealer (SMS 45) is uniquely design with balance combination of Film Forming and Penetrating sealer to form excellent waterproofing properties on treated surface. Suitable use on interior and exterior concrete, masonry, natural stone and wood.

### **GENERAL SPECIFICATION**

<b>Paint Code</b>	<b>SUNCOT Multi Sealer (SMS 45)</b>
<b>Touch Dry Time</b>	<b>20-30 minutes</b>
<b>Full Cure Time</b>	<b>3 hours</b>
<b>Recoat Time</b>	<b>Above 3 hours</b>
<b>Coverage</b>	<b>As wall or floor primer</b> <ul style="list-style-type: none"><li>• 10-12 m<sup>2</sup>/kg ( 1 coat)</li><li>• 5-6 m<sup>2</sup>/kg ( 2 coat)</li></ul> <b>As Waterproofing</b> <ul style="list-style-type: none"><li>• 2.5-3.0 m<sup>2</sup>/kg ( 2 coat)</li></ul>

<b>Manufacturer's Name &amp; Address</b>	<b>SUNWAY COATING SOLUTIONS SDN BHD</b> <b>NO 17 , JALAN TPP 6/11,</b> <b>TAMAN PERINDUSTRIAN PUCHONG, SEKSYEN 6 BATU 12,</b> <b>47100 PUCHONG, SELANGOR DARUL EHSAN, MALAYSIA.</b>
<b>Telephone</b>	<b>+603 8066 8510</b>
<b>Emergency Telephone No.</b>	<b>+603 8066 8510</b>



**TRADING &  
MANUFACTURING**

**SUNWAY COATING SOLUTIONS SDN BHD 200201024249  
A member of Sunway Group**

**APPLICATION PROCEDURE**

- (a) Surface Preparation – Surface clean and dry to apply**
- (b) Paint Mixing**  
The mixture should be stirred for at least 5-10 minutes to ensure homogeneity.
- (c) Dilution Ratio**  
- Dilution not necessary
- (d) Number of Coats Recommended**  
- 2 coats depending on application methods.
- (g) Application Methods**  
- Brush, Roller, Conventional Air Spray and Airless Spray.
- (h) Consumption**  
2.5 - 3.0 kg/m<sup>2</sup>
- (i) Drying Schedule / 25-30 °C.**  
Dry to touch ----- 20-30 minutes.  
Dry to overcoat ----- Minimum 3 hours  
Dry to handle ----- 24 hours

The thicker the paint film, the longer the curing time. However, higher temperature will shorten while lower temperature will lengthen the curing time.

**DISCLAIMER:**

All the above information and/or recommendation are given to the best of our present knowledge and ability when properly stored, handled and applied under normal conditions in accordance with SUNWAY COATING SOLUTIONS recommendations.

The information only applies to the application(s) and product(s) expressly referred to herein. In case of changes in the parameters of the application, such as changes in substrates etc., or in case of a different application, consult SUNWAY COATING SOLUTIONS. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.